

# Q4i UAV

## Aerial Vehicle (AV) + Characteristics

---

UAV Weight with battery and max. payload <3.5 Kg

---

UAV Size with Propeller < 80 cm X 80 cm

---

Endurance (upto 1000m AMSL Take-Off) 40 minutes with Day payload (upto 1000m AMSL Takeoff)

---

Range of live transmission (LOS) 4 km (un-obstructed & interference free)

---

Typical Cruise Speed 7 m/s

---

Propulsion Battery Powered Electric Propulsion

---

Maximum operating altitude (AGL) 400m AGL (Above Ground Level)

---

Maximum launch altitude (AMSL) 3000m AMSL (Above Mean Sea Level)

---

Functional Temperature Range 0°C to +50°C (OEM Certification)

---

Dust & Drizzle Resistance IP 53 rating (OEM Certification)

# Q4i UAV

---

Aural Signature	<40 Db @300 meters AGL (OEM Certification)
Wind Resistance	Upto 10m/s (36kmph or ~20knots)
Technical Life of UAV (Landings)	Minimum 500 landings (OEM Certification)
Launch & Recovery	Autonomous Vertical Take-Off & Landing (VTOL)
Maximum space required for recovery	25m x 25m open area
Autonomy	Fully autonomous from Take-off to Landing without using any R/C controller
Flight Modes	Altitude Hold Hover at a defined waypoint Autonomous Waypoint Navigation (pre-defined as well as dynamically adjustable waypoints during flight) Remotely Piloted mode (RPV Mode) OPTIONAL
Operating Crew	Maximum 2
Deployment Time	< 10 minutes
Packaging and Storage	Waterproof Backpacks to carry all mission critical components with IP66 or better rating for dust and drizzle protection (OEM-certification)

---

# Q4i UAV

---

Failsafe features

Auto-Return to Home and Land on Communication Failure  
Auto-Return to Home and Land on Low Battery  
Multiple GPS on-board for redundancy  
Auto-Return to Home and Land on exceeding Wind limit of the system  
Auto-Return to Home and Land on Battery Imbalance  
Auto-Return to Home and Land on exceeding the UAV health parameters (Temperature, vibration and throttle limit of the system)

---

Navigation Lights

Switchable (from GCS)

---

## Payload Characteristics

---

Payload Options

Daylight HD (1280X720) with 10x optical zoom video payload  
Thermal 320X240 video payload (Optional)  
Thermal 640X480 video payload (Optional)  
Photogrammetry RX0 payload, fixed mount (Optional)

---

Video Stabilization

Electronic and Gimbal stabilization of video output at all zoom levels in real-time (Applicable only with surveillance payload)

---

Payload Replacement Time

< 5 minutes

---

Payload Control (in flight)

Pan: 360° continuous (with UAV) Tilt: 90° (Only with surveillance payload)

# Q4i UAV

---

Target Detection Slant Range (Human Size Target) Daylight: Minimum 800m Thermal(640X480): Minimum 400m Thermal(320X240): Minimum 200m

## Ground Control Station (GCS)

---

3D Maps

OPTIONAL (WITH 3D CAPABILITY) Switchable between 2D/3D map views, capability to tilt/rotate 3D map as per user input

---

GUI Display parameters

Geographic Map along with UAV location, UAV trajectory, camera view polygon, waypoints and flight plan (Applicable only for surveillance payloads) Real-time video from the UAV with on-screen display of important parameters like UAV co-ordinates, target (payload) co-ordinates and range from UAV, true North indication, Distance from HOME, etc. (Applicable only for surveillance payloads) Real-time video displayed at all times during the flight (Applicable only for surveillance payloads) Artificial Horizon indicating UAV attitude

---

Maps

Capability of working with some publicly available open-source maps. Application has the capability to download maps automatically after specifying location GPS co-ordinates 2D Maps: Capability to integrate geo-referenced raster maps provided in at least one of the commonly used digital map formats (eg. GIF TIFF) as well as shape file (.shp) OPTIONAL (WITH 3D CAPABILITY) Capability to integrate SRTM and DTED based elevation data

---

Terrain Avoidance

Detects and avoids natural terrain by using elevation data (where available)

# Q4i UAV

---

Free Hand Annotation	Capability to annotate a desired location on the map screen.
Terrain Hugging	Capability to maintain uniform altitude separation from ground during navigation over non-uniform terrain
No Fly Zone	Ability for user to mark zones which they do not desire the UAV to enter during flight. Also highlights airports in the vicinity and restricts UAV from entering those areas
Geo Fencing	Capability in creating a virtual fence/perimeter for a real-world geographical area. It enables the user in creating a predefined boundary to avoid the RPA venturing beyond the defined area accidentally.
Channel Scan	Ability to estimate the best suited channel for a desired location based on the colour indication for effective flight operations.
User Controls	Take-off/Land without any manual assistance Set altitude of the UAV Waypoint navigation Dynamic flight plan adjustment Point payload to ground coordinate function (Applicable only in surveillance payloads) RPV Mode which allows UAV to be flown in semi autonomous mode
Joystick Controls	Full camera controls - Pan/Tilt & Zoom In/Out (Applicable only for surveillance payloads) RPV mode Altitude control
Video	Video recorded on the GCS and exported in commonly portable video format (AVI/MP4 etc.). (Applicable only for surveillance payloads) Video of

---

# Q4i UAV

---

the full flight is recorded by default with option to turn recording off (Applicable only for surveillance payloads) Capability of taking image snapshots with on-screen display parameters at any time during flight (Applicable only for surveillance payloads)

---

Pre-flight checks

Capability to perform pre-flight checks of the complete system before every flight for confirming the suitability of flightworthiness

---

Others

Essential telemetry data logging Export of flight path in .kml format for reviewing in Google Earth

---

## Optional GCS Features

---

Remote Video Streaming

OPTIONAL - Stream Live Video from GCS to remote location over Internet or local network. - Option of ONVIF stream and control at remote location for 3rd party VMS integration. (Applicable only for surveillance payloads)

---

Moving Target Indication

OPTIONAL - Highlight moving objects in live video display. (Applicable only for surveillance payloads)

---

## Communication link

---

Type

Laptop or Tablet

# Q4i UAV

---

Screen Size

Min. 10" diagonal

---

Functional Temperature Range

0°C to +50°C (OEM certification)

---

GCS Controller Battery back-up

Atleast 2 full endurance flight without spare battery

---

IP Rating

IP53

---

## **Recommended GCS Controller Specification**

---

Communication link capabilities

Transmit control commands from GCS to UAV  
Transmit telemetry data from UAV GCS Transmit  
day and night video from UAV to GCS (Applicable  
only for surveillance payloads) Secure  
Communication link between UAV and GCS with  
128-bit AES encryption Digital and Encrypted

---

Auto Tracking Comm Box

Auto tracking directional antenna

---

Frequency Band

2.4GHz or 5GHz (depending on application)